



- NOTES:
1. MATERIAL:
 - 1.1 HOUSING: SEE TABLE, UL94V-0; COLOR: BLACK,LCP.
 - 1.2 CONTACT: BRASS(C2680),T=0.20mm.
 - 1.3 SHELL: SUS304,T=0.30mm.
 2. FINISH:
 - 2.1 CONTACT: 1u"MIN. GOLD PLATING ON CONTACT AREA. 50u" MIN NICKEL UNDERPLATING OVERALL.
 - 2.2 SHELL: OVERALL NICKEL PLATING 50u" MIN.
 3. RECOMMENDED P.C.B THICKNESS: 0.80±0.05
 4. REFLOW SOLDER CAPABLE TO 260°C.
 5. "X" SHOWS Cpk MEASUREMENT ITEMS.
 6. "O" SHOWS FAI MEASUREMENT ITEMS.
 7. "I" SHOWS QIP INSPECTION ITEMS.

41-41075-XXXHF
 HF: HALOGEN FREE
 HOUSING COLOR: 1: WHITE,LCP
 2: RED(186C),PA10T
 3: BLACK,LCP
 PLATING CODE: 0: Au30u" 1: G/F(1u")
 2: Au5u" 3: Au10u"
 4: Au15u" 5: Au20u"

RECOMMEN PCB LAYOUT COMPONENT SIDE
 TOLERANCE±0.05mm P.C.B THICKNESS 0.80mm

41-41075-03HF	BLACK	LCP
41-41075-02HF	RED(186C)	PA10T
41-41075-01HF	WHITE	LCP
P/N	COLOR	HOUSING

TOLERANCE:
 X ± 0.50 X° ± 1°
 X ± 0.38 X° ± 1°
 .XX ± 0.25 .XX° ± 1.0°
 .XXX±0.13

UNIT: MM

TXF 同心富
 Shenzhen TXF Precision Electronics Co., Ltd.

深圳市同心富精密电子有限公司

DRAW: Eva Chen 2016. 11. 18P/N: TXFPB1701104
 SCALE: 1/1
 CHECK: 1:1
 APPR: 1:1

ITEM: MICRO USB 5Pin 夹板式(加E)

LTR	ECN NO	REVISION	RECORD	DRAW	DATE
1	2	3	4	5	6