



料号备注:
C-TF459-LH46XXL

- "01" 镀金1U
 - "02" 镀金3U
 - "03" 镀金5U
 - "04" 镀金15U
 - "05" 镀金30U
 - "06" 半金锡1U
 - "09" 半金锡15U
 - "10" 半金锡30U
- "Y" 哑镍
"L" 亮镍

1. MATERIAL
HOUSING: LCP, UL94V-0, BLACK
CONTACT: COPPER ALLOY, T=0.15
SHELL: STAINLESS STEEL, T=0.3
COVER: STAINLESS STEEL, T=0.25
2. FINISH
CONTACT: 50U" MIN NICKEL UNDERPLATING OVERALL
GOLD PLATING SELECTIVE ON CONTACT AREA
50U" MIN TIN PLATING ON SOLDER TAIL
SHELL: 40U" MIN NICKEL UNDERPLATING OVERALL
COVER: 40U" MIN NICKEL UNDERPLATING OVERALL
3. ELECTRICAL
CURRENT: 1.0A
VOLTAGE: 30V
CONTACT RESISTANCE: 50 MILLIOHMS MAX.
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC
INSULATION RESISTANCE: 100 MEGOHMS MIN.
4. MECHANICAL
MATING FORCE: 35N MAX.
UNMATING FORCE: 10N MIN, INITIAL.
8N AFTER 10000 CYCLES.
DURABILITY: 10000 CYCLES
5. PRODUCT NO. DESCRIPTION:

TOLERANCE:		UNIT	深圳市同心富精密电子有限公司 Shenzhen TXF Precision Electronics Co., LTD			
X. ±0.50	X. ° ±1°	MM				
.X ±0.35	.X ° ±1°	SHEET	DRAW: CHEN 2017.08.26 P/N: C-TF459-LH46XXL DESIGN: CHEN 2017.08.26 ITEM: MICRO USB 5P BF SMT 1.6.3 垫高CL=4.15(脚长1.0)			
.XX ±0.25	.XX ° ±1.0°	1/1				
.XXX ±0.10		SCALE	CHECK: CHEN 2017.08.26	REV: A APPR:		
		1:1				
		REV: A	DRW NO: C-24035			

LTR	ECN NO	REVISION	RECORD	DRAW	DATE